



2.0-2.5T

Nissan K25 Engine ;

China Wanfeng Engine ;

Impco or BRC Converter ;

CE, EPA, ISO Certificate ;

Product Specification:

Model	Power type	Rated capacity (kg)	Load center (mm)	Lift height (mm)	Engine		Rated output (kw/rpm)	Transmission
					Model	Manufacture		
CPQD20N-RW11-Y	Gasoline /LPG	2000	500	3000	K25	NISSAN	44/2500	CHINA
CPQD25N-RW11-Y	Gasoline /LPG	2500	500	3000	K25	NISSAN	44/2500	CHINA
CPQD20N-RW11A-Y	Gasoline /LPG	2000	500	3000	K25	NISSAN	44/2500	NISSAN
CPQD25N-RW11A-Y	Gasoline /LPG	2500	500	3000	K25	NISSAN	44/2500	NISSAN
CPQD20N-RW11B-Y	Gasoline /LPG	2000	500	3000	K25	NISSAN	44/2500	OKAMURA
CPQD25N-RW11B-Y	Gasoline /LPG	2500	500	3000	K25	NISSAN	44/2500	OKAMURA
CPQD20N-RW20-Y	Gasoline /LPG	2000	500	3000	K25	NISSAN	36.8/2600	CHINA
CPQD25N-RW20-Y	Gasoline /LPG	2500	500	3000	K25	NISSAN	36.8/2600	CHINA
CPQD20N-RW26-Y	Gasoline /LPG	2000	500	3000	K25	GM3.0L	50/2500	CHINA
CPQD25N-RW26-Y	Gasoline /LPG	2000	500	3000	K25	GM3.0L	50/2500	CHINA
CPQD20N-RW7-Y	Gasoline /LPG	2000	500	3000	491GP	WANFENG	41/2800	CHINA
CPQD25N-RW7-Y	Gasoline /LPG	2500	500	3000	491GP	WANFENG	41/2800	CHINA

Advantages:

Appearance

The latest appearance design method was used to create the R series fluent and aesthetic outline, which matches the latest appearance trend.

Efficiency

Thanks to the long wheelbase design, the longitudinal stability of whole truck is much better, the hoisting capacity at same lift height are enhanced by an average of 100KG compared with former truck. At the same time, it prolongs work time of rear wheel as the reduced rear axle's load.

The travel speed of truck has been raised, for example, the 2-2.5T type comes to 20km/h.

Service

Dual air spring supporting hood and one-touch removal of the floorboard get you right to service operations, and reduces down-time.

The reasonable arrangement of fuse and installation of instrument, enable the replacing for fuse and maintenance for instrument easier.

Clean

The environment friendly engines all meet EU stage-2 emission control regulation. The noise emission also comes to EU standard. The metal hood and molding sound insulation matches environmental protection demands.

Safe

A throttling device is set in pipe system—the mast won't result in failing control of mast even some pipes broke. By using a built-in hood lock device, the safe level of the truck has been raised.

Mast specification:

Type	Model	Max. fork Height mm	Overall height		Free lift		Tilt range		
			Lowered mm	Extended Without backrest mm	With Backrest mm	Without backrest mm	With backrest mm	FWD Deg	RWD Deg
	R25M250	2500	1735	3125	3545	150	150	6	12
	R25M270	2700	1835	3325	3745	150	150	6	12
	R25M300	3000	1985	3625	4045	150	150	6	12
	R25M330	3300	2135	3925	4345	150	150	6	12
Wide view mast	R25M350	3500	2235	4125	4545	150	150	6	12
	R25M360	3600	2335	1225	4645	150	150	6	12
	R25M400	4000	2585	1625	5045	150	150	6	12
	R25M430	4300	2735	1925	5345	150	150	6	6
	R25M450	4500	2835	5125	5545	150	150	6	6
	R25M480	4800	2985	5425	5845	150	150	6	6
	R25M500	5000	3085	5625	6045	150	150	6	6
Wide view full free	N25U250	2500	1795	3152	3545	1143	750	6	12
	N25U270	2700	1895	3352	3745	1243	850	6	12
	N25U300	3000	1995	3652	4045	1343	950	6	12
	N25U330	3300	2145	3952	4345	1493	1100	6	12
2stage mast	N25U360	3600	2295	4252	4645	1643	1250	6	12
	N25U400	4000	2545	4652	5045	1893	1500	6	12
Wide view full free	N25N430	4300	2040	4992	5355	1358	995	6	6
	N25N450	4500	2110	5242	5605	1428	1065	6	6
	N25N480	4800	2210	5492	5855	1528	1165	6	6
	N25N500	5000	2275	5692	6055	1593	1230	6	6
3stage mast	N25N550	5500	2440	6192	6555	1758	1395	3	6
	N25N600	6000	2655	6692	7055	1973	1610	3	6