



3.0-3.5T

Nissan K25 Engine ;

China Wanfeng Engine ;

Impco or BRC Converter ;

CE, EPA, ISO Certificate ;

Product Specification:

Model	Power type	Rated capacity (kg)	Load center (mm)	Lift height (mm)	Engine			
					Model	Manufacture	Rated output (kw/rpm)	Transmission
CPQD30N-RW11	Gasoline	3000	500	3000	K25	NISSAN	44/2500	CHINA
CPQD35N-RW11	Gasoline	3500	500	3000	K25	NISSAN	44/2500	CHINA
CPQD30N-RW11A	Gasoline	3000	500	3000	K25	NISSAN	44/2500	NISSAN
CPQD35N-RW11A	Gasoline	3500	500	3000	K25	NISSAN	44/2500	NISSAN
CPQD30N-RW11B	Gasoline	3000	500	3000	K25	NISSAN	44/2500	OKAMURA
CPQD35N-RW11B	Gasoline	3500	500	3000	K25	NISSAN	44/2500	OKAMURA
CPQD30N-RW7	Gasoline	3000	500	3000	491GP	WANFENG	41/2800	CHINA
CPQD35N-RW7	Gasoline	3500	500	3000	491GP	WANFENG	41/2800	CHINA

Advantages:

Appearance

The latest appearance design method was used to create the R series fluent and aesthetic outline, which matches the latest appearance trend.

Efficiency

Thanks to the long wheelbase design, the longitudinal stability of whole truck is much better, the hoisting capacity at same lift height are enhanced by an average of 100KG compared with former truck. At the same time, it prolongs work time of rear wheel as the reduced rear axle's load.

The travel speed of truck has been raised, for example, the 2-2.5T type comes to 20km/h.

Turning radius and width of right angle stacking aisle are decreased through reducing the dimensions of whole

truck, that raise the efficiency of storehouse.

Service

Dual air spring supporting hood and one-touch removal of the floorboard get you right to service operations, and reduces down-time.

The reasonable arrangement of fuse and installation of instrument, enable the replacing for fuse and maintenance for instrument easier.

Clean

The environment friendly engines all meet EU stage-2 emission control regulation. The noise emission also comes to EU standard.

The metal hood and molding sound insulation matches environmental protection demands.

Safe

A throttling device is set in pipe system—the mast won't result in failing control of mast even some pipes broke. By using a built-in hood lock device, the safe level of the truck has been raised.

Mast specification:

Type	Model	Max. fork Height mm	Overall height						Free lift				Tilt range	
			Lowered		Extended		With backrest		Without backrest		With backrest		FWD	RWD
			3T	3.5T	3T	3.5T	3T	3.5T	3T	3.5T	3T	3.5T	Deg	Deg
Wide view mast	R30/35M250	2500	1760	1910	3165	3310	3630	3630	155	155	155	155	6	12
	R30/35M270	2700	1860	2010	3365	3510	3830	3830	155	155	155	155	6	12
	R30/35M300	3000	2010	2160	3665	3810	4130	4130	155	155	155	155	6	12
	R30/35M330	3300	2160	2310	3965	4110	4430	4430	155	155	155	155	6	12
	R30/35M350	3500	2260	2410	4165	4310	4630	4630	155	155	155	155	6	12
	R30/35M360	3600	2370	2460	4265	4410	4730	4730	155	155	155	155	6	12
	R30/35M400	4000	2620	2710	4665	4810	5130	5130	155	155	155	155	6	12
	R30/35M430	4300	2770	2860	4965	5110	5430	5430	155	155	155	155	6	6
	R30/35M450	4500	2870	2960	5165	5310	5630	5630	155	155	155	155	6	6
	R30/35M480	4800	3020	3110	5465	5610	5930	5930	155	155	155	155	6	6
R30/35M500	5000	3120	3120	5665	5810	6130	6130	155	155	155	155	6	6	
Wide view full free 2stage mast	N30/35U250	2500	1865	1975	3235	3370	3635	3640	1130	1115	730	845	6	12
	N30/35U270	2700	1965	2075	3435	3570	3835	3840	1230	1215	830	945	6	12
	N30/35U300	3000	2190	2190	3760	3860	4140	4130	1435	1330	1060	1060	6	12
	N30/35U330	3300	2225	2375	4045	4170	4445	4440	1490	1515	1090	1245	6	12
	N30/35U360	3600	2375	2540	4345	4470	4745	4740	1640	1670	1240	1400	6	12
	N30/35U400	4000	2575	2740	4745	4870	5145	5140	1840	1870	1440	1600	6	12
Wide view full free 3stage mast	N30/35N430	4300	2090	2205	5050	5105	5445	5440	1355	1395	960	1060	6	6
	N30/35N450	4500	2160	2260	5300	5305	5695	5640	1425	1465	1030	1130	6	6
	N30/35N480	4800	2260	2354	5550	5605	5945	5940	1525	1565	1130	1230	6	6
	N30/35N500	5000	2326	2420	5750	5805	6145	6140	1590	1630	1196	1295	6	6
	N30/35N550	5500	2490	2605	6250	6305	6645	6640	1755	1795	1360	1460	3	6
	N30/35N600	6000	2656	2770	6750	6805	7145	7140	1920	1960	1525	1625	3	6